

Tools & Accessories



Nail-in Pipe Clips

ref	size	pack qty
PPS123	Ø15mm	10
PPS223	Ø22mm	10



PTFE Tape

ref	size	pack qty
PPS01	12mm x 12m (approx)	1



Gas PTFE Tape

ref	size	pack qty
GF10	12mm x 12m (approx)	1



Brass Radiator Key

ref	size	pack qty
PPS02	5mm (3/16")	2



Easy Grip Radiator Key

ref	size	pack qty
PPS12	5mm (3/16")	1



Arctic Spray Pipe Freezer

ref	description	pack qty
S158	240g - Can	1
S159	Ø8-15mm Starter Kit	1



Pipe Cutter

ref	description	pack qty
PB777	Lightweight cutter	1



www.levante-products.com

Polyfit is the one step, fully demountable and reusable pushfit plumbing product, which combines with white polybutylene pipe to create a truly flexible, yet highly secure, plumbing system that is demountable and reusable when required.

Approvals and Applications

- WRAS Listed in the WRAS Water Fittings and Materials Directory
- Standards Manufacturing Quality Assurance - in accordance with BS EN ISO 9002 (BSI registered firm Certificate FM00318)
- Installation Standard - to follow the requirements of BS5955 - PART 8 2001 Plastic pipework (Thermoplastic Materials)
- British Standard - Class S rated to BS7291 Part 1 and Kitemark Licence Number 38148 to BS7291 Part 1 & 2
- British Gas - has accepted the Polyfit Class S Polybutylene pipe system as being acceptable for open vented and sealed central heating systems and are eligible for acceptance onto Home Care Central Heating System Cover
- Suitable for use in hot and cold water and heating systems in domestic properties
- Polyfit fittings should be used with white Polyfit pipes and other Polypipe specialist pipe systems such as conduit pipe

Your nearest distributor:



Technical Helpline: 01302 765563

Or for further information, email info@levante-products.com

LEV0383/04.16

Plumbing Solutions



Quickfix Push Fit Plumbing

PolyFit is a hand demountable white, push fit plumbing system, offering maximum flexibility and adjustability.

PolyFit features a one step jointing operation for quick and easy installation. PolyFit leads the market in speed to fit.

If you need to adjust a fitting joint during the installation process, PolyFit fittings can be quickly demounted by hand, or by using a release tool.

Use PolyFit with Polypipe white polybutylene flexible pipe, using a Polypipe metal or plastic pipe stiffener. For extra security, choose the new Polypipe sealed stiffener.

PolyFit can be used on a wide range of contract and retrofit projects, including hot and cold water systems, and is particularly suitable for first fix installations.

Straight Coupler

ref	size	pack qty
OFIT015	Ø15mm	1
OFIT022	Ø22mm	1

Reducing Coupler

ref	size	pack qty
OFIT5822	Ø22 - Ø15mm	1

Equal Tee

ref	size	pack qty
OFIT215	Ø15mm	1
OFIT222	Ø22mm	1

Reducing Tee

ref	size	pack qty
OFIT1122	Ø22 - Ø22 - Ø15mm	1

Elbow

ref	size	pack qty
OFIT115	Ø15mm	1
OFIT122	Ø22mm	1

Socket Reducer

ref	size	pack qty
OFIT1822	Ø22 - Ø15mm	1

Socket Blank End

ref	size	pack qty
OFIT1915-2	Ø15mm	2
OFIT1922-2	Ø22mm	2

Spigot Blank End

ref	size	pack qty
OFIT915-2	Ø15mm	2
OFIT922-2	Ø22mm	2

Pipe Stiffener

ref	size	pack qty
OFIT6415-4	Ø15mm	4
OFIT6422-4	Ø22mm	4

Shut-off Valve

ref	size	pack qty
OFIT5915	Ø15 - Ø15mm	1

Stopcock

ref	size	pack qty
OFIT2615	Ø15mm	1

Barrier Pipe



ref	size	pack qty
OFIT215B	Ø15mm x 2m	10
OFIT222B	Ø22mm x 2m	10

Hoses

The Polyfit hose connector range provides the choice of length, end connection and valve options, suitable for a wide range of projects.

Many of the flexible connectors include the PolyFit one step joint feature, which are quick and easy to install and are ideal for use in tricky to reach or tight locations.

All PolyFit hoses which have a tap connector nut contain captive rubber seals, ensuring that seals are not lost or damaged on site.

Quickfix Flexi Hose Tap Connector



ref	size	pack qty
OFIT6815	Ø15mm x 1/2" x 300mm	1
OFIT681534	Ø15mm x 3/4" x 300mm	1
OFIT6822	Ø22mm x 3/4" x 300mm	1

Flexible Tap Connector



ref	size	pack qty
PF95	Ø15mm x 1/2" x 300mm	1
PF281	Ø15mm x 3/4" x 300mm	1
PF96	Ø22mm x 3/4" x 300mm	1

Note: These hoses are not suitable for use with central heating.